



Distributed By:

www.envirotechlighting.com

888-760-4422

LED Troffer – Volumetric Troffer – ANGLE-5 Series

ANGLE-5

Applications: Offices, Hospitals, Retail, Universities

Product Features:

- LED Saves 40-50% of energy over fluorescent T8/T5.
- Simple, tool-less installation with easy access to components for future maintenance, upgrades.
- Die formed of 24 gauge cold-rolled steel body. Post-painted and powder coated with high gloss baked white enamel finish.
- LED Class-2 Driver with 120-277v and 0-10V Standard Dimming.
- Design Lights Consortium V4.0 PREMIUM – Qualified Product
- 5 years warranty, 100,000hrs Lifespan



Product Specifications:

LED TYPE: LG 5630 “HE” LED

- WATTS: 2x4: 27.5W, 41W
- EFFICACY: > 150 Lm/W
- CRI: > 84
- COLOR TEMP: 4000K Standard
 - (Optional 3000K, 5000K)

LED DRIVER: Fulham Class-2 Driver

- VOLTAGE: 120-277v
- FREQUENCY: 50/60Hz
- POWER FACTOR: > 0.99
- THD: < 10%
- 0-10v Dimming (included)

MOUNTING

- Retrofit into existing recessed Parabolic, Prismatic and Direct/Indirect Troffers or Mount in T-Bar as new fixture.

Warranty: 5 Years



Size	Model	Watts	Lumens
2 x 2	L	27.5W	4,100 Lm
1 x 4	L	27.5W	3,600 Lm
2 x 4	L	27.5W	4,200 Lm
2 x 4	M	42W	5,600 Lm

DLC Listed by J2 Light Inc
 Category: 2x4, 2x2, 1x4 Luminaires
 Classification: DLC Premium
 Part Codes:
 AL22L41 > AL22L31
 AL214L41 > AL214M31
 AL224L41 > AL224L31
 AL224M41 > AL224M31



ORDER CODES:

A - _____ - _____ - _____

<u>Size</u>	<u>Wattage</u>	<u>Color Temp</u>
AL222 = 2x2	L = 27.5W	41 = 4100K
AL214 = 1x4	M = 42W	31 = 3000K (special order)
AL224 = 2x4		

