

## LED Radial Strip – LRS Series



**Applications:** Warehouses, Manufacturing, Parking Garages, Retail

**Product Features:**

- LED Saves 60-75% of energy over HID and 40-50% over T8/T5HO
- Die formed of 24 gauge cold-rolled steel body, post painted with high gloss baked white matte power painted.
- V-Clips for Dual Point Chain or Cable Hanging.
- High Power LM80 Approved LG Gen 4 LED's
- ESPEN Class-2 Constant Current UL Listed Dimmable LED Driver
- 0-10V standard dimming, optional Bi-Level Occupancy Sensor
- UL/cUL Listed, RoHS Compliant
- **DesignLights Consortium (DLC)** Listed – v3.0 Premium  
*(part codes listed in box below)*
- 5 years warranty, 100,000hrs Lifespan



**Product Specifications:**

**LED TYPE:** LG Gen 4

- **WATTS:**
  - 4' – 22w, 40w, 50w
  - 8' – 40w, 68w
- **EFFICACY:** > 110 Lm/W
- **CRI:** > 80 Ra
- **COLOR TEMP:** 5000K (Optional 3000K, 3500K, 4000K)
- **BEAM ANGLE:** 200 dg

**LED DRIVER:** ESPEN Constant Current

- **VOLTAGE:** 120-277v
- **FREQUENCY:** 50/60Hz
- **POWER FACTOR:** > 0.95
- **THD:** < 20%
- 0-10v Dimming (included)

**MOUNTING:** Surface Mount or Provided V-hooks

**OPTIONS:** Occupancy Sensor, Bi-Level, Emergency

**Warranty:** 5 Years

Length	Watts	Lumens
4'	23w	2,990
	50w	5,500
8'	40w	4,600
	67w	7,650

Manufacturer: EnviroTech Lighting

DLC Part Codes:

- ENV-LRS-4L-4K/5K
- ENV-LRS-4VH-4K/5K
- ENV-LRS-8L-35K/4K/5K\*\*
- ENV-LRS-8H-35K/4K/5K\*\*

\*\*Also listed as "Low Bay"



**ORDER CODES:**

ENV-LRS-

<u>Length/Wattage</u>	<u>Color Temp</u>	<u>Options</u>
4L = 23W	5K = 5000K	OS = Occ Sensor
4VH = 50W	4K = 4000K **	BL = Bi-Level
8L = 40W	3K = 3000K **	EM = Emergency Driver
8H = 67W	35K = 3500K **	
	** Special Order	

