

LED Radial Strip – LRSRK Series Retrofit Kit

LRSRK

Applications: Warehouses, Manufacturing, Parking Garages, Retail

Product Features:

- LED Saves 60-75% of energy over HID and 40-50% over T8/T5HO
- Die formed of 24 gauge cold-rolled steel body, post painted with high gloss baked white matte power coat.
- Attaches to standard Fluorescent Strip lights from 4.25" to 5.25" wide.
- High Power LM80 Approved LG Gen 4 LED's
- ESPEN Class-2 Constant Current UL Listed Dimmable LED Driver
- 0-10V standard dimming, optional Bi-Level Occupancy Sensor
- UL/cUL Listed, RoHS Compliant
- **DesignLights Consortium (DLC)** Listed – v3.0 Premium
(part codes listed in box below)
- 5 years warranty, 100,000hrs Lifespan



Product Specifications:

LED TYPE: LG Gen 4

- **WATTS:**
 - 4' – 22w, 40w, 50w
 - 8' – 40w, 68w
- **EFFICACY:** > 110 Lm/W
- **CRI:** > 80 Ra
- **COLOR TEMP:** 5000K (Optional 3000K, 3500K, 4000K)
- **BEAM ANGLE:** 200 dg

LED DRIVER: ESPEN Constant Current

- **VOLTAGE:** 120-277v
- **FREQUENCY:** 50/60Hz
- **POWER FACTOR:** > 0.95
- **THD:** < 20%
- 0-10v Dimming (included)

MOUNTING: Attaches to existing Fluorescent Channel

OPTIONS: Occupancy Sensor, Bi-Level, Emergency

Length	Watts	Lumens
4'	22w	2,530
	40w	4,400
	50w	5,500
8'	40w	4,600
	67w	7,650

Manufacturer: EnviroTech Lighting

DLC Part Codes:

- ENV-LRSRK-4L-4K/5K
- ENV-LRSRK-4H-4K/5K
- ENV-LRSRK-8L-4K/5K**
- ENV-LRSRK-8H-4K/5K**

**Also listed as "Low Bay"



Warranty: 5 Years

ORDER CODES:

ENV-LRSRK-

Length/Wattage

- 4L = 22W
- 4H = 40W
- 4VH = 50W
- 8L = 40W
- 8H = 67W

Color Temp

- 5K = 5000K
- 4K = 4000K **

** Special Order

Options

- OS = Occ Sensor
- BL = Bi-Level
- EM = Emergency Driver

