

LED Troffer – Volumetric Retrofit – LTVRK Series

LTVRK

Applications: Offices, Hospitals, Retail, Universities

Product Features:

- LED Saves 50%-60% of energy over fluorescent T8/T5.
- Retrofits Fluorescent recessed troffers in minutes – with no need to dispose of existing fixture body.
- Simple, tool-less installation with easy access to components for future maintenance, upgrades.
- Die formed of 22 gauge cold-rolled steel body. Post-painted and powder coated with high gloss baked white enamel finish.
- High transmission diffused opaque lens gives uniform light output.
- LED Class-2 Driver with 120-277v and 0-10V Standard Dimming.
- **DesignLights Consortium (DLC) Pending** – v4.0 Premium
- 5 years warranty, 100,000hrs Lifespan



Product Specifications:

LED TYPE: LG 5630 “HE” LED

- WATTS: 2x2: 18W, 23W
2x4: 23W, 34W
- EFFICACY: > 132+ Lm/W

- CRI: > 80
- COLOR TEMP: 4000K Standard
 - (Optional 3500K, 5000K)

LED DRIVER: ESPEN Class-2 Driver

- VOLTAGE: 120-277v
- FREQUENCY: 50/60Hz
- POWER FACTOR: > 0.90
- THD: < 10%
- 0-10v Dimming (included)

MOUNTING

- Retrofit into existing recessed Parabolic, Prismatic and Direct/Indirect Troffers

Warranty: 5 Years

Size	Model	Watts	Lumens
2 x 2	L	18W	2400 Lm
2 x 2	H	23W	3100 Lm
2 x 4	L	23W	3100 Lm
2 x 4	H	34W	4500 Lm

Manufacturer:

EnviroTech Lighting/Jiangsu Ever-Tie Lighting Co. Ltd

DLC Part Codes:

- ENV-LTVRK-24-H-XK / ETLTRK-24/HLP/23/YDM XXXX (A1,A3+B3)
- ENV-LTVRK-22-H-XK / ETLTRK-22/HLP/23/YDM XXXX (A1A3+B3)

ORDER CODES:

ENV-LTVRK-

Size

22 = 2x2

24 = 2x4

Wattage

L = 18W (2x2)

H = 23W (2x2)

L = 23W (2x4)

M = 34W (2x4)

Color Temp

4K = 4000K

3K = 3500K **

5K = 5000K **

** Special Order

