



www.envirotechlighting.com

888-760-4422

LED Vapor Tight – LVT Series



Applications: Food Processing/Storage, Parking Garages, Freezers

Product Features:

- LED saves 60-75% of energy over HID and 40-50% over T8/T5HO.
- Three-piece design allows for tool-less assembly.
- Injection molded polycarbonate housing with liquid silicone continuous gasket provides long life and waterproof operation.
- 100% UV Stabilized Diffuser with crystallized lens allows for maximum, even light distribution.
- High Power LM80 Approved LG Gen 4 LED's
- ESPEN Class-2 Constant Current UL Listed Dimmable LED Driver
- UL/cUL Listed, RoHS Compliant
- Optional Microwave Sensor for Bi-Level Dimming
- **DesignLights Consortium (DLC) Listed – v3.0 Premium**
(part codes listed in box below)
- 5 years warranty, 100,000hrs Lifespan



Product Specifications:

LED TYPE: LG Gen 4

- **WATTS:**
 - 4' – 40w, 55w
- **EFFICACY:** > 120 Lm/W
- **CRI:** > 83
- **COLOR TEMP:** 5000K (Optional 3000K, 4000K)
- **BEAM ANGLE:** 200 dg

LED DRIVER: ESPEN Constant Current

- **VOLTAGE:** 120-277v
- **FREQUENCY:** 50/60Hz
- **POWER FACTOR:** > 0.90
- **THD:** < 10%
- 0-10v Dimming (included)

MOUNTING: Surface Mount or Chain Mounted

Warranty: 5 Years



Length	Watts	Lumens
4'	40w	5,000
	55w	7,100

Manufacturer: EnviroTech Lighting

DLC Part Codes:

- ENV-LVT-4L-3K/4K/5K
- ENV-LVT-4H-3K/4K/5K



ORDER CODES:

ex) ENV-LWP32-60-5K

ENV-LVT-

Length/Wattage

4L = 40W
4H = 55W

Color Temp

5K = 5000K
4K = 4000K
3K = 3000K

Options

BL = Bi-Level

