



Distributed By:

www.envirotechlighting.com

888-760-4422

LED Linear Highbay – SPaRo 5 Series

SPaRo 5

Applications: Warehouse, Manufacturing, Automotive, Retail

Product Features:

- LED Saves 60-75% of energy over HID and 40-50% over T8/T5HO
- Die formed 24 gauge cold-rolled steel body. All steel surface are post-painted with high gloss baked white matte power painted.
- V-Clips for Dual Point Chain or Cable Hanging.
- Tool-Less Hinged bottom LED Driver access doors.
- Included high transmission opaque acrylic lens.
- High Power LM80 Approved Samsung Gen 5 LED's
- Fulham Class-2 Constant Current UL Listed Dimmable LED Driver
- Optional **Occupancy/Daylight Sensor** for Off/On or Bi-Level Control
- **DesignLights Consortium** (DLC) Listed – v4.0 Premium *(part codes listed in box below)*
- 5 years warranty, 100,000hrs Lifespan



Product Specifications:

LED TYPE: Samsung S5 or similar

- WATTS: 95W, 109W, 142W
- EFFICACY: > 135+ Lm/W
- CRI: > 80+
- COLOR TEMP: 5000K Standard

LED DRIVER: Fulham Class-2 Driver @ 525mA

- VOLTAGE: 120-277v
- FREQUENCY: 50/60Hz
- POWER FACTOR: > 0.99
- THD: < 10%
- 0-10v Dimming (included)

MOUNTING

- Retrofit Jack Chain or Aircraft Cable Suspension

Warranty: 5 Years



Model	Watts	Lumens
S513K1	95W	13,000 Lm
S520K1	142W	20,000 Lm

ORDER CODES:

S5 _____ - _____ - _____

Watt/Lumen Color Temp Options

13K1 = 95W 50 = 5000K OC = Occ Sensor

20K1 = 142W BL = Bi-Level

